



Xerox DocuColor
2060
west products company
ph: (800) 455-4189

advanced **DOCUCOLOR**

DC
2060



This is one of the fastest digital **COLOR** printers available on Earth and it is within your reach. The **XEROX DOCUCOLOR 2060** prints 60 pages of superior color per minute.

The **Docucolor 2060** uses advanced color processes which result in vibrant color output. Faithfully reproducing your files with depth and range, it prints full bleed 11x17/A3 jobs for a variety of finished products you wouldn't expect a digital press to handle. Never before could you print from your disk or desktop and expect offset quality production waiting in a matter of minutes, not days.

The **Xerox DocuColor 2060** is fully loaded and ready to compete in an offset world. Able to print heavier paperstocks (up to 280 gsm./ 12pt) and run for longer periods of unattended printing, the Docucolor 2060 is poised to be a serious printing solution for corporations that demand the best quality now, not tomorrow.

Contact: **West Products Company**
with questions, prices or purchasing
information about the **DocuColor 2060**
phone: **(800) 455-4189**
docucolor2060@westproducts.com

® XEROX 2000 series DOCUCOLOR 2060.

docucolor 2060



Xerox® DocuColor 2060 specifications

Performance

Print Resolution	600x600 dpi
Printing Speed	60 ppm
Maximum Page Size	12.5"x19.2"
Printing Technology	Color Laser

Paper Handling

Maximum Input (sheets)	3,150
Default RIP System	Creo-Scitex
Duplex	included
Monthly volume	120,000
Minimum paper weight (lbs)	61 GSM
Maximum paper weight (lbs)	280 GSM
Standard paper trays	4

Options:

- 2,500 Sheet High Capacity Feeder
- 2,250 Sheet HC Stacker / Stapler
- 4,000 Sheet High Capacity Stacker
 - Integrated Digital Scanner
- Duplexing Auto Document Feeder

Features:

- Auto Color Select
- Auto Color Calibration
- Auto Contrast
- Auto Paper Select
- Auto Tray Switching
- Auto Covers
- Book Copying
- Margin Shift, Auto Center
- Mirror Image, Negative
- Multi-Up / Posters
- Stored Jobs
- Automatic Image Rotation
- TRACS - LOFT - Digital Blanket
- I-Tracs

Networking:

- Via RiIP systems:
- Fiery EX2000 or Creo-Scitex CSX2000
- Mac OS 8+, MSWindows, NT, Unix, Sun
- Solaris, Splash

Input Media Types

- 16 lb. bond to 12pt index stock (280gsm),
- Transparency, Carbonless, Pre-drilled Stock,
- Pressure Sensitive Labels, and other
- Specialty Stocks.

Xerox® DocuColor 2060

Electrical Requirements

Electronic Subsystem
(Creoscitex 2000)
115 VAC 60 Hz.



15 AMP Edison Receptacle
NEMA #5-15R

DocuColor 2060 Printer
(printing system)
208-240 VAC., 60 Hz.



30 AMP
(NEMA #14-30R)

Electrical Requirements:

Current Service: 30 amps
(sole use)
Frequency: 60 Hz

warmup time: 7.4 minutes

Environmental Requirements:

Operating Temperatures:
Minimum: 50 degrees F
Maximum: 94 degrees F
Humidity: 15%-85% +/- 5%

Heat Dissipation:

Standby: 4080 (1.8kW) BTU/hr
Operating: 2720 (2.6kW) BTU/hr

For Sales, Parts, Service or Refabrication Contact

West Products Company

(800) 455-4189 2180 Las Palmas Drive Carlsbad, CA 92009
product information - www.westproducts.com