

WPC
westproducts.com



**Xerox Docucolor
30**

west products company
ph: (800) 455-4189

advanced **DOCUCOLOR**

**DC
30**

30 pages
per minute
full color
digital
printer/copier



The Xerox® Docucolor 30 gives you a serious full color printer with the speed and power to handle those demanding digital print runs.

Here is the perfect digital solution for companies that require small to medium quantities of full color printing.

The **Docucolor 30** combines an award-winning print engine with a wide selection of digital front ends, network capabilities and productivity-boosting accessories. Offices and professional printers can appreciate the powerful mix of speed and economy the **Docucolor 30** offers in a very small package.

The **Xerox DocuColor 30** is fast, 30 pages per minute. That's more productivity and profit per minute than most digital color printers. Teamed with auto sorting, auto duplexing, user friendly interfaces and a capacity to print on a wide range of media, you'll find the Docucolor 30 is the perfect addition for companies who demand a lot from their color printers.

Contact West Products Comany and see how we can make the Docucolor 30 affordable for your company.

docucolor 30



Performance

Print Resolution	400x400 dpi
Printing Speed	30 ppm
Maximum Page Size	12"x18"
Printing Technology	Color Laser

Paper Handling

Maximum Input (sheets)	1,550
Maximum Output (sheets)	Optional Sorter
Duplex	included
Monthly volume	100,000
Minimum paper weight (lbs)	61 GSM
Maximum paper weight (lbs)	105 GSM
Standard paper trays	3

Bypass Tray: Maximum weight (105 GSM) and heavy specialty stocks can be run via the Bypass Tray.

specifications

Client Environments Supported

- DOS 5.0 - 6.2.
- Windows 3.1, 3.11, Windows 95/98, Windows NT, Windows 2000
- Mac OS 7.x, 8.x and 9.x
- Sun OS 4.1.3 / Solaris 1.1.1B.
- Solaris 2.3 / 2.4 / 2.5.1 / 2.6.

PDLs and Data Formats

- Adobe PostScript Level 3/PDF.
- PCL 5e. • TIFF. • ASCII

Native Network Environments

- TCP/IP.
- Ethernet
- AppleTalk.
- Novell (SPX-IPX).

Printer Options

Optional Collation, Optional Automatic Document Feeder. Reduction-enlargement 25%-400%, Optional edit pad and pen.

Input Media Types

16 lb. bond to 28 lb bond., Transparency, Carbonless, Pre-drilled Stock, Pressure Sensitive Labels, and other Specialty Stocks.

Xerox® DocuColor 30

Electrical Requirements

Electronic Subsystem
(Fiery Controller)
115 VAC 60 Hz.



15 AMP Edison Receptacle
NEMA #5-15R

Electrical Requirements:
Current Service: 30 amps
(sole use)
Frequency: 60 Hz

Power Consumption:
Maximum: 2.6 kVA
Standby: 1.8kW

warmup time: 7.4 minutes

DocuColor 30 Printer
208/240 VAC, 50/60 Hz.
Wall Receptacle



30 AMP
NEMA #14-30R

Environmental Requirements:
Operating Temperatures:
Minimum: 50 degrees F
Maximum: 90 degrees F
Humidity: 45% +/- 5%

Heat Dissipation:
Standby: 6143 (1.8kW) BTU/hr
Operating: 8874 (2.6kW) BTU/hr

For Sales, Parts, Service or Refurbishing Contact
West Products Company

(800) 455-4189 2180 Las Palmas Drive Carlsbad, CA 92009
product information - www.westproducts.com