



Xerox Docucolor 40

west products company
ph: (800) 455-4189

advanced **DOCUCOLOR**

DC 40

40 pages
per minute
full color
digital
printer/copier



The Xerox® Docucolor 40 offers full color laser printing at unbelievable speeds

Surpassing the industry demands color solutions that produce elite quality in small to medium quantities, the **Docucolor 40** creates an explosive growth market you can harness. Combine an award-winning print engine with a wide selection of digital front ends, out of the box network capabilities and productivity-boosting accessories, and you have a powerful solution for short-run color printing, copying and network printing.

The Xerox DocuColor 40 is a very fast and versatile machine. The DC-40 offers 40 pages per minute of full color printing. That's more productivity and profit per minute than any other digital color copier or printer. Teamed with auto sorting, auto duplexing, user friendly interfaces and a capacity to print on a wide range of media, and **West Products Company** can make it affordable for your business.

docucolor 40



Performance

Print Resolution	400x400 dpi
Printing Speed	40 ppm
Maximum Page Size	12"x18"
Printing Technology	Color Laser

Paper Handling

Maximum Input (sheets)	1,550
Maximum Output (sheets)	Optional Sorter
Duplex	included
Monthly volume	100,000
Minimum paper weight (lbs)	61 GSM
Maximum paper weight (lbs)	105 GSM
Standard paper trays	3

Bypass Tray.: Maximum weight (105 GSM) and heavy specialty stocks can be run via the Bypass Tray.

specifications

Client Environments Supported

- DOS 5.0 - 6.2.
- Windows 3.1,3.11, Windows 95/98, Windows NT, Windows 2000
- Mac OS 7.x, 8.x and 9.x
- Sun OS 4.1.3 / Solaris 1.1.1B.
- Solaris 2.3 / 2.4 / 2.5.1 /2.6.

PDLs and Data Formats

- Adobe PostScript Level 3/PDF.
- PCL 5e. • TIFF. • ASCII

Native Network Environments

- TCP/IP.
- Ethernet
- AppleTalk.
- Novell (SPX-IPX).

Printer Options

Optional Collation, Optional Automatic Document Feeder. Reduction-enlargement 25%-400%, Optional edit pad and pen.

Input Media Types

16 lb. bond to 28 lb bond., Transparency, Carbonless, Pre-drilled Stock, Pressure Sensitive Labels, and other Specialty Stocks.

Xerox® DocuColor 40

Electrical Requirements

Electronic Subsystem

(Fiery Controller)
115 VAC 60 Hz.



15 AMP Edison Receptacle
NEMA #5-15R

Electrical Requirements:

Current Service: 30 amps
(sole use)
Frequency: 60 Hz

Power Consumption:

Maximum: 2.6 kVA
Standby: 1.8kW

warmup time: 7.4 minutes

DocuColor 40 Printer

208/240 VAC, 50/60 Hz.
Wall Receptacle



30 AMP
NEMA #14-30R

Environmental Requirements:

Operating Temperatures:
Minimum: 50 degrees F
Maximum: 90 degrees F
Humidity: 45% +/- 5%

Heat Dissipation:

Standby: 6143 (1.8kW) BTU/hr
Operating: 8874 (2.6kW) BTU/hr

For Sales, Parts, Service or Refurbishing Contact

West Products Company

(800) 455-4189 2180 Las Palmas Drive Carlsbad, CA 92009
product information - www.westproducts.com